



B1D05120E

1200V ▲ 5A ▲ SiC SCHOTTKY DIODE

SILICON CARBIDE SiC SCHOTTKY DIODE ▲ SMD type

Excellent surge capability

Easy paralleling due to positive V_F temperature coefficient

TO-252-2L (DPAK) package ▲ Epoxy meets UL94-V0 ▲ MSL3








Low forward voltage

Temperature independent switching



SPECIFICATION

Item ($T_C = 25^\circ\text{C}$, unless otherwise noted)		Characteristics
Operating Temperature Range	T_J	-55°C to $+175^\circ\text{C}$
Storage Temperature Range	T_S	-55°C to $+175^\circ\text{C}$
Repetitive Peak Reverse Voltage	V_{RRM}	1200V
Continuous Forward Current at $T_C = 160^\circ\text{C}$	I_F	5A
Total Capacitive Charge ($T_J = 25^\circ\text{C}$)	Q_C	32nC
Capacitance Stored Energy ($V_R = 800\text{V}$)	E_C	16μJ
Diode Forward Voltage ($T_J = 175^\circ\text{C}$, $I_F = 5\text{A}$)	V_F	1.78V
Power Dissipation	P_{TOT}	124W

APPLICATIONS

EV Charging	Industrial Inverters	Motors & Drives	Power Factor Correction	Renewable Energy	SMPS	UPS
						

PIN DESCRIPTION

Circuit Diagram	Outline - Top View	Pin No.	Description
		1 2	Cathode (Case Backside) Anode

ABSOLUT MAXIMUM RATINGS ▲ $T_C = 25^\circ\text{C}$, unless otherwise noted

Item	Condition	Symbol		Unit
Repetitive Peak Reverse Voltage		V_{RRM}	1200	V
Non-Repetitive Peak Reverse Voltage		V_{RSM}	1200	V
Continuous Forward Current	$T_C = 25^\circ\text{C}$	I_F	23	A
Continuous Forward Current	$T_C = 160^\circ\text{C}$	I_F	5	A
Non-Repetitive Forward Surge Current	$T_C = 25^\circ\text{C}$, $t_p = 10\text{ms}$, Half Sine Wave	I_{FSM}	60	A
I^2t Value	$T_C = 25^\circ\text{C}$, $t_p = 10\text{ms}$	$\int i^2 dt$	18	A^2s
Power Dissipation	$T_C = 25^\circ\text{C}$	P_{TOT}	124	W
Power Dissipation	$T_C = 110^\circ\text{C}$	P_{TOT}	53	W
Operating Junction Temperature		T_J	-55 to +175	$^\circ\text{C}$
Storage Temperature Range		T_{STG}	-55 to +175	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS

Item	Condition	Symbol	Min.	Typ.	Max.	Unit
Static Characteristics						
DC Blocking Voltage	$T_J = 25^\circ\text{C}$	V_{DC}	1200			V
Diode Forward Voltage	$I_F = 5\text{A}$, $T_J = 25^\circ\text{C}$	V_F		1.40	1.60	V
Diode Forward Voltage	$I_F = 5\text{A}$, $T_J = 175^\circ\text{C}$	V_F		1.78	2.45	V
Reverse Current	$V_R = 1200\text{V}$, $T_J = 25^\circ\text{C}$	I_R		2	48	μA
Reverse Current	$V_R = 1200\text{V}$, $T_J = 175^\circ\text{C}$	I_R		10	100	μA

Item	Condition	Symbol	Min.	Typ.	Max.	Unit
Dynamic Characteristics						
Total Capacitive Charge	$V_R = 800\text{V}$, $T_J = 25^\circ\text{C}$ $Q_C = \int_0^{V_R} C(V) dV$	Q_C		32		nC
Total Capacitance	$V_R = 1\text{V}$, $f = 1\text{MHz}$, $T_J = 25^\circ\text{C}$	C		352		pF
Total Capacitance	$V_R = 400\text{V}$, $f = 1\text{MHz}$, $T_J = 25^\circ\text{C}$	C		32		pF
Total Capacitance	$V_R = 800\text{V}$, $f = 1\text{MHz}$, $T_J = 25^\circ\text{C}$	C		23		pF
Capacitance Stored Energy	$V_R = 800\text{V}$, $T_J = 25^\circ\text{C}$	E_C		16		μJ

THERMAL RESISTANCE PERFORMANCE

Item	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance, Junction to Case	$R_{\theta JC}$		1.207		K/W

REFERENCE DATA ▲ TYPICAL PERFORMANCE

Fig. 1 • Typical Forward Characteristics I_F vs. V_F




Fig. 2 • Typical Reverse Current I_R as function of Reverse Voltage V_R




Fig. 3 • Diode Forward Current I_F as function of Case Temperature T_C (D = Duty Cycle)




Fig. 4 • Typical Capacitance C as function of Reverse Voltage V_R , $C = f(V_R)$, $T_J = 25^\circ\text{C}$, $f = 1\text{MHz}$




Fig. 5 • Typical Reverse Charge Q_C as function of Reverse Voltage V_R







Fig. 6 • Power Dissipation P_{TOT} as function of Case Temperature T_C




REFERENCE DATA ▲ TYPICAL PERFORMANCE

Fig. 7 • Capacitance Stored Energy


Fig. 8 • Maximum Transient Thermal Impedance, $Z_{thjc} = f(t)$, Parameter: $D = t/T$


PACKAGE OUTLINE




Sym	Millimeters (Min.)	Millimeters (Typ.)	Millimeters (Max.)
A	2.20	2.30	2.38
A1	0.00	-	0.20
A2	0.90	1.07	1.17
b	0.68	0.78	0.90
b3	5.23	5.33	5.46
c	0.43	0.53	0.61
D	5.98	6.10	6.22
D1	5.30 REF		
E	6.40	6.60	6.73
E1	4.63	-	-

Sym	Millimeters (Min.)	Millimeters (Typ.)	Millimeters (Max.)
e		2.286 BSC	
H	9.40	10.10	10.50
L	1.38	1.50	1.75
L1	2.90 REF		
L2	0.51 BSC		
L3	0.88	-	1.28
L4	0.50	.	1.00
L5	1.65	1.80	1.95
θ	0°	-	8°

ORDERING INFORMATION

Part Number	Package	Packing	Reel Qty.	Inner Box Qty.	Outer Box Qty.
B1D05120E	TO-252-2L (DPAK)	Reel	2,500pcs	5,000pcs	30,000pcs

RECOMMENDED PAD LAYOUT




Sym	Millimeters (Min.)	Millimeters (Typ.)	Millimeters (Max.)	Sym	Millimeters (Min.)	Millimeters (Typ.)	Millimeters (Max.)
F1	-	6.00	-	F5	-	2.29	-
F2	-	6.25	-	F6	-	1.40	-
F3	-	1.40	-	F7	-	3.00	-
F4	-	2.29	-	F8	-	6.50	-


Notes:

1. The suggested land pattern dimensions have been provided for reference only.
2. For further information, please reference document IPC-7351A.

PART MARKING




REEL AND TAPE DIMENSIONS ▲ All dimensions in mm



Package	W	A	B	C	d1	D	E	F	P	P0	T	D	D1	D2	G	W1
TO252-2L	16.00 ±0.30	6.90 ±0.10	10.50 ±0.10	2.70 ±0.10	1.50 Max.	1.50 ±0.10	1.75 ±0.10	7.50 ±0.10	8.00 ±0.10	4.00 ±0.10	0.30 ±0.10	330 ±0.30	50 Min.	13.00 ±0.50	16.40 Min.	22.00 Min.

Note: All dimensions meet EIA-481-D requirements.

RECOMMENDED REFLOW SOLDERING PROFILE



Recommended reflow soldering conditions ▲ Refer to JEDEC J-STD-020E

Profile Features		Sn-Pb Eutetic Assembly	Pb-Free Assembly
Preheat temperature min.	$T_{s \min}$	100 °C	150 °C
Preheat temperature max.	$T_{s \max}$	150 °C	200 °C
Preheat time t_s from $T_{s \min}$ to $T_{s \max}$	t_s	120 seconds	120 seconds
Ramp-up rate (T_L to T_p)		max. 3 °C/second	max. 3 °C/second
Liquidous temperature	T_L	183 °C	217 °C
Time t_L maintained above T_L	t_L	150 seconds max.	150 seconds max.
Peak package body temperature	T_p	235°C	260°C
Timeframe of within 5°C below and up to max actual peak body temperature	t_p	20 seconds max.	30 seconds max.
Ramp-down rate (T_L to T_p)		max. 6 °C/second	max. 6 °C/second
Time 25°C to peak temperature		max. 6 minutes	max. 8 minutes

REVISION TABLE

Revision	Date	Status	Notes
001	30/09/2022	Initial release	Initial publication

DISCLAIMER

Except for the written expressed warranties, MGT does not implicitly, by assumption or whatever else, warrant, under-take, promise any other warranty or guaranty for any MGT product.

All information and technical specifications made available by MGT are for guidance only and we reserve the right to change or modify them without prior notice. Unless expressly stated in writing by MGT, we reject any guarantees, obligations, or warranties.

All MGT products with the technical specifications described are suitable for use in certain applications. Operating, production, storage and environmental conditions can have a massive influence on the parameters mentioned in the data sheets, which cause the performance to vary over time.

It is subject to the user's duty of care to design and validate his products in such a way that appropriate measures are taken, such as protective circuits or redundant systems to ensure the safety standards required in the application.

MGT components are not designed or rated for use in life support, rescue, safety critical, military, or aerospace applications where failure or malfunction could result in property or environmental damage, serious injury or death. In the aforementioned cases, please contact us before using MGT products.

In principle, we reserve all rights and MGT's general terms and conditions apply. You can find them on our website www.mgt.co.com.