



# B2D06065E

650V ▲ 6A ▲ SiC SCHOTTKY DIODE

SILICON CARBIDE SiC SCHOTTKY DIODE ▲ SMD type

Excellent surge capability

Easy paralleling due to positive  $V_F$  temperature coefficient

TO-252-2L (DPAK) package ▲ Epoxy meets UL94-V0 ▲ MSL3








Temperature independent switching

Ultra-low forward voltage and high surge current



## SPECIFICATION

Item ( $T_C = 25^\circ\text{C}$ , unless otherwise noted)		Characteristics
Operating Temperature Range	$T_J$	$-55^\circ\text{C}$ to $+175^\circ\text{C}$
Storage Temperature Range	$T_S$	$-55^\circ\text{C}$ to $+175^\circ\text{C}$
Repetitive Peak Reverse Voltage	$V_{RRM}$	650V
Continuous Forward Current at $T_C = 160^\circ\text{C}$	$I_F$	6A
Total Capacitive Charge ( $T_J = 25^\circ\text{C}$ )	$Q_C$	17nC
Capacitance Stored Energy ( $V_R = 400\text{V}$ )	$E_C$	4.5μJ
Diode Forward Voltage ( $T_J = 175^\circ\text{C}$ , $I_F = 6\text{A}$ )	$V_F$	1.63V
Power Dissipation	$P_{TOT}$	107W

## APPLICATIONS

EV Charging	Industrial Inverters	Motors & Drives	Power Factor Correction	Renewable Energy	SMPS	UPS
						

## PIN DESCRIPTION

Circuit Diagram	Outline - Top View	Pin No.	Description
		1 2	Cathode (Case Backside) Anode

## ABSOLUT MAXIMUM RATINGS ▲ $T_C = 25^\circ\text{C}$ , unless otherwise noted

Item	Condition	Symbol		Unit
Repetitive Peak Reverse Voltage		$V_{RRM}$	650	V
Non-Repetitive Peak Reverse Voltage		$V_{RSM}$	650	V
Continuous Forward Current	$T_C = 25^\circ\text{C}$	$I_F$	24	A
Continuous Forward Current	$T_C = 160^\circ\text{C}$	$I_F$	6	A
Non-Repetitive Forward Surge Current	$T_C = 25^\circ\text{C}$ , $t_p = 10\text{ms}$ , Half Sine Wave	$I_{FSM}$	48	A
$I^2t$ Value	$T_C = 25^\circ\text{C}$ , $t_p = 10\text{ms}$	$\int i^2 dt$	11.52	$\text{A}^2\text{s}$
Power Dissipation	$T_C = 25^\circ\text{C}$	$P_{TOT}$	107	W
Power Dissipation	$T_C = 110^\circ\text{C}$	$P_{TOT}$	46	W
Operating Junction Temperature		$T_J$	-55 to +175	$^\circ\text{C}$
Storage Temperature Range		$T_{STG}$	-55 to +175	$^\circ\text{C}$

## ELECTRICAL CHARACTERISTICS

Item	Condition	Symbol	Min.	Typ.	Max.	Unit
<b>Static Characteristics</b>						
DC Blocking Voltage	$T_J = 25^\circ\text{C}$	$V_{DC}$	650			V
Diode Forward Voltage	$I_F = 6\text{A}$ , $T_J = 25^\circ\text{C}$	$V_F$		1.33	1.50	V
Diode Forward Voltage	$I_F = 6\text{A}$ , $T_J = 175^\circ\text{C}$	$V_F$		1.63	2.10	V
Reverse Current	$V_R = 650\text{V}$ , $T_J = 25^\circ\text{C}$	$I_R$		1	70	$\mu\text{A}$
Reverse Current	$V_R = 650\text{V}$ , $T_J = 175^\circ\text{C}$	$I_R$		15	150	$\mu\text{A}$

Item	Condition	Symbol	Min.	Typ.	Max.	Unit
<b>Dynamic Characteristics</b>						
Total Capacitive Charge	$V_R = 400\text{V}$ , $T_J = 25^\circ\text{C}$ $Q_C = \int_0^{V_R} C(V) dV$	$Q_C$		17		nC
Total Capacitance	$V_R = 1\text{V}$ , $f = 1\text{MHz}$ , $T_J = 25^\circ\text{C}$	$C$		271		pF
Total Capacitance	$V_R = 300\text{V}$ , $f = 1\text{MHz}$ , $T_J = 25^\circ\text{C}$	$C$		30.1		pF
Total Capacitance	$V_R = 600\text{V}$ , $f = 1\text{MHz}$ , $T_J = 25^\circ\text{C}$	$C$		29.8		pF
Capacitance Stored Energy	$V_R = 400\text{V}$ , $T_J = 25^\circ\text{C}$	$E_C$		4.5		$\mu\text{J}$

## THERMAL RESISTANCE PERFORMANCE

Item	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance, Junction to Case	$R_{\theta JC}$		1.401		K/W

# REFERENCE DATA ▲ TYPICAL PERFORMANCE

Fig. 1 • Typical Forward Characteristics  $I_F$  vs.  $V_F$




Fig. 2 • Typical Reverse Current  $I_R$  as function of Reverse Voltage  $V_R$




Fig. 3 • Diode Forward Current  $I_F$  as function of Case Temperature  $T_C$  (D = Duty Cycle)




Fig. 4 • Typical Capacitance  $C$  as function of Reverse Voltage  $V_R$ ,  $C = f(V_R)$ ,  $T_J = 25^\circ\text{C}$ ,  $f = 1\text{MHz}$




Fig. 5 • Typical Reverse Charge  $Q_C$  as function of Reverse Voltage  $V_R$





Fig. 6 • Power Dissipation  $P_{TOT}$  as function of Case Temperature  $T_C$



## REFERENCE DATA ▲ TYPICAL PERFORMANCE

Fig. 7 • Capacitance Stored Energy






Fig. 8 • Maximum Transient Thermal Impedance,  $Z_{thjc} = f(t)$ , Parameter:  $D = t/T$



## PACKAGE OUTLINE




Sym	Millimeters (Min.)	Millimeters (Typ.)	Millimeters (Max.)
A	2.20	2.30	2.38
A1	0.00	-	0.20
A2	0.90	1.07	1.17
b	0.68	0.78	0.90
b3	5.23	5.33	5.46
c	0.43	0.53	0.61
D	5.98	6.10	6.22
D1	5.30 REF		
E	6.40	6.60	6.73
E1	4.63	-	-

Sym	Millimeters (Min.)	Millimeters (Typ.)	Millimeters (Max.)
e		2.286 BSC	
H	9.40	10.10	10.50
L	1.38	1.50	1.75
L1	2.90 REF		
L2	0.51 BSC		
L3	0.88	-	1.28
L4	0.50	.	1.00
L5	1.65	1.80	1.95
θ	0°	-	8°

## ORDERING INFORMATION

Part Number	Package	Packing	Reel Qty.	Inner Box Qty.	Outer Box Qty.
B2D06065E	TO-252-2L (DPAK)	Reel	2,500pcs	5,000pcs	25,000pcs

## RECOMMENDED PAD LAYOUT




Sym	Millimeters (Min.)	Millimeters (Typ.)	Millimeters (Max.)	Sym	Millimeters (Min.)	Millimeters (Typ.)	Millimeters (Max.)
F1	-	6.00	-	F5	-	2.29	-
F2	-	6.25	-	F6	-	1.40	-
F3	-	1.40	-	F7	-	3.00	-
F4	-	2.29	-	F8	-	6.50	-


### Notes:

1. The suggested land pattern dimensions have been provided for reference only.
2. For further information, please reference document IPC-7351A.

## PART MARKING




## REEL AND TAPE DIMENSIONS ▲ All dimensions in mm



Package	W	A	B	C	d1	D	E	F	P	P0	T	D	D1	D2	G	W1
TO252-2L	16.00 ±0.30	6.90 ±0.10	10.50 ±0.10	2.70 ±0.10	1.50 Max.	1.50 ±0.10	1.75 ±0.10	7.50 ±0.10	8.00 ±0.10	4.00 ±0.10	0.30 ±0.10	330 ±0.30	50 Min.	13.00 ±0.50	16.40 Min.	22.00 Min.

**Note:** All dimensions meet EIA-481-D requirements.

## RECOMMENDED REFLOW SOLDERING PROFILE



### Recommended reflow soldering conditions ▲ Refer to JEDEC J-STD-020E

Profile Features		Sn-Pb Eutetic Assembly	Pb-Free Assembly
Preheat temperature min.	T <sub>s min</sub>	100 °C	150 °C
Preheat temperature max.	T <sub>s max</sub>	150 °C	200 °C
Preheat time t <sub>s</sub> from T <sub>s min</sub> to T <sub>s max</sub>	t <sub>s</sub>	120 seconds	120 seconds
Ramp-up rate (T <sub>L</sub> to T <sub>p</sub> )		max. 3 °C/second	max. 3 °C/second
Liquidous temperature	T <sub>L</sub>	183 °C	217 °C
Time t <sub>L</sub> maintained above T <sub>L</sub>	t <sub>L</sub>	150 seconds max.	150 seconds max.
Peak package body temperature	T <sub>p</sub>	235°C	260°C
Timeframe of within 5°C below and up to max actual peak body temperature	t <sub>p</sub>	20 seconds max.	30 seconds max.
Ramp-down rate (T <sub>L</sub> to T <sub>p</sub> )		max. 6 °C/second	max. 6 °C/second
Time 25°C to peak temperature		max. 6 minutes	max. 8 minutes



## REVISION TABLE

Revision	Date	Status	Notes
001	30/09/2022	Initial release	Initial publication

## DISCLAIMER

Except for the written expressed warranties, MGT does not implicitly, by assumption or whatever else, warrant, under-take, promise any other warranty or guaranty for any MGT product.

All information and technical specifications made available by MGT are for guidance only and we reserve the right to change or modify them without prior notice. Unless expressly stated in writing by MGT, we reject any guarantees, obligations, or warranties.

All MGT products with the technical specifications described are suitable for use in certain applications. Operating, production, storage and environmental conditions can have a massive influence on the parameters mentioned in the data sheets, which cause the performance to vary over time.

It is subject to the user's duty of care to design and validate his products in such a way that appropriate measures are taken, such as protective circuits or redundant systems to ensure the safety standards required in the application.

MGT components are not designed or rated for use in life support, rescue, safety critical, military, or aerospace applications where failure or malfunction could result in property or environmental damage, serious injury or death. In the aforementioned cases, please contact us before using MGT products.

In principle, we reserve all rights and MGT's general terms and conditions apply. You can find them on our website [www.mgt.co.com](http://www.mgt.co.com).