

CED6072AL

60V ▲ 6.7mΩ ▲ 50A ▲ Si MOSFET

SILICON Si MOSFET ▲ THT type

N-channel enhancement mode

UL94V-0 rated flame retardant epoxy

TO251 (E-PAK) package

Super high dense cell density for extremely low $R_{DS(ON)}$

High power and current handling capability






MAXIMUM RATINGS

Parameter ($T_C = 25^\circ\text{C}$, unless otherwise noted)		Characteristics
Drain-Source Voltage	V_{DS}	60V
Gate-Source Voltage	V_{GS}	$\pm 20\text{V}$
Continuous Drain Current at $T_C = 25^\circ\text{C}$	I_D	50A
Continuous Drain Current at $T_C = 100^\circ\text{C}$	I_D	31.5A
Pulsed Drain Current ^{Note 1}	I_{DM}	200A
Maximum Power Dissipation at $T_C = 25^\circ\text{C}$	P_D	35.7W
Power Dissipation Derating above 25°C	ΔP_D	$0.28\text{W}/^\circ\text{C}$
Single Pulsed Avalanche Energy ^{Note 4}	E_{AS}	112.5mJ
Single Pulsed Avalanche Current ^{Note 4}	I_{AS}	15A
Operating and Storage Temperature Range	T_J, T_{STG}	-55°C to $+150^\circ\text{C}$



THERMAL CHARACTERISTICS

Parameter	Symbol	Limit
Thermal Resistance, Junction-to-Case	R_{TH_JC}	$3.5^\circ\text{C}/\text{W}$
Thermal Resistance, Junction-to-Ambient	R_{TH_JA}	$50^\circ\text{C}/\text{W}$

APPLICATIONS

Battery Management Systems	DC/DC Converter	DC Fan	Industrial Control	Power Switches
				

PIN DESCRIPTION

Circuit Diagram	Outline - Front View	Pin No.	Description
		1 2 3	Gate Drain Source

ELECTRICAL CHARACTERISTICS ▲ $T_C = 25^\circ\text{C}$, unless otherwise noted

Item	Condition	Symbol	Min.	Typ.	Max.	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	$V_{GS} = 0V, I_D = 250\mu A$	BV_{DSS}	60			V
Zero Gate Voltage Drain Current	$V_{DS} = 60V, V_{GS} = 0V$	I_{DSS}			1	μA
Gate Body Leakage Current, Forward	$V_{GS} = 20V, V_{DS} = 0V$	I_{GSSF}			100	nA
Gate Body Leakage Current, Reverse	$V_{GS} = -20V, V_{DS} = 0V$	I_{GSSR}			-100	nA
On Characteristics ^{Note 2}						
Gate Threshold Voltage	$V_{GS} = V_{DS}, I_D = 250\mu A$	$V_{GS(th)}$	1.2		2.5	V
Static Drain-Source On-Resistance	$V_{GS} = 10V, I_D = 4A$	$R_{DS(ON)}$		6.7	8	m Ω
Static Drain-Source On-Resistance	$V_{GS} = 4.5V, I_D = 3A$	$R_{DS(ON)}$		8.8	11	m Ω
Dynamic Characteristics ^{Note 3}						
Input Capacitance	$V_{DS} = 25V, V_{GS} = 0V, f = 1MHz$	C_{ISS}		865		pF
Output Capacitance	$V_{DS} = 25V, V_{GS} = 0V, f = 1MHz$	C_{OSS}		315		pF
Reverse Transfer Capacitance	$V_{DS} = 25V, V_{GS} = 0V, f = 1MHz$	C_{RSS}		5		pF
Switching Characteristics ^{Note 3}						
Turn-On Delay Time	$V_{DD} = 30V, V_{GS} = 10V, I_D = 1A, R_{G(ext)} = 6\Omega$	$t_{D(ON)}$		15		ns
Turn-On Rise Time	$V_{DD} = 30V, V_{GS} = 10V, I_D = 1A, R_{G(ext)} = 6\Omega$	t_R		4		ns
Turn-Off Delay Time	$V_{DD} = 30V, V_{GS} = 10V, I_D = 1A, R_{G(ext)} = 6\Omega$	$t_{D(OFF)}$		37		ns
Turn-Off Fall Time	$V_{DD} = 30V, V_{GS} = 10V, I_D = 1A, R_{G(ext)} = 6\Omega$	t_F		18		ns
Total Gate Charge	$V_{DS} = 48V, V_{GS} = 4.5V, I_D = 20A$	Q_G		7.7		nC
Gate Source Charge	$V_{DS} = 48V, V_{GS} = 4.5V, I_D = 20A$	Q_{GS}		2.2		nC
Gate Drain Charge	$V_{DS} = 48V, V_{GS} = 4.5V, I_D = 20A$	Q_{GD}		4.2		nC
Drain-Source Diode Characteristics and Maximum Ratings						
Drain-Source Diode Forward Current		I_S			29	A
Drain-Source Diode Forward Voltage	$V_{GS} = 0V, I_S = 20A$	V_{SD}			1.2	V

Notes

- 1: Repetitive Rating: Pulse width limited by maximum junction temperature.
- 2: Pulse Test: Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$.
- 3: Guaranteed by design, not subject to production testing.
- 4: $L = 1mH, I_{AS} = 15A, V_{DD} = 24V, R_G = 25\Omega$, Starting $T_J = 25^\circ\text{C}$

REFERENCE DATA ▲ TYPICAL DEVICE PERFORMANCE

Fig. 1 • Output Characteristics




Fig. 2 • Transfer Characteristics




Fig. 3 • Capacitance




Fig. 4 • On-Resistance Variation with Temperature




Fig. 5 • Gate Threshold Variation with Temperature





Fig. 6 • Body Diode Forward Voltage Variation with Source Current



REFERENCE DATA ▲ TYPICAL DEVICE PERFORMANCE

Fig. 7 • Gate Charge




Fig. 8 • Maximum Safe Operating Area




Fig. 9 • Breakdown Voltage Variation vs. Temperature




Fig. 10 • Switching Test Circuit






Fig. 11 • Switching Waveforms




REFERENCE DATA ▲ TYPICAL DEVICE PERFORMANCE

Fig. 12 • Normalized Thermal Transient Impedance Curve



PACKAGE OUTLINE




Sym	Millimeters (Min.)	Millimeters (Typ.)	Millimeters (Max.)
A	2.180	-	2.400
A1	0.860	-	1.500
b	0.700	-	0.960
b1	0.700	-	0.860
C	0.400	-	0.610
D1	5.400	-	6.630
E	6.050	-	7.010
E1	4.950	-	5.460
e	1.980	-	2.590
F	0.400	-	0.890
L	8.500	-	9.650
L1	0.500	-	1.800

ORDERING INFORMATION


Part Number	Package	Packing	Tube Qty.	Inner Box Qty.	Outer Box Qty.
CED6072AL	TO251 (E-PAK)	Tube	80pcs	4,000pcs	16,000pcs

PART MARKING



DATE CODE

Example: 11S4Z



Coding list for „Day“

1	2	3	4	5	6	7	8	9	A
01	02	03	04	05	06	07	08	09	10
B	C	D	E	F	G	H	I	J	K
11	12	13	14	15	16	17	18	19	20
L	M	N	O	P	Q	R	S	T	U
21	22	23	24	25	26	27	28	29	30
V									
31									


Coding list for „Month“

1	2	3	4	5	6
Jan	Feb	Mar	Apr	May	Jun
7	8	9	A	B	C
Jul	Aug	Sep	Oct	Nov	Dec

Coding list for „Year“

0	1	2	3	4
2020	2021	2022	2023	2024
5	6	7	8	9
2025	2026	2027	2028	2029

RECOMMENDED WAVE SOLDERING PROFILE ▲ THT PACKAGE



Classification wave soldering profile ▲ Refer to EN 61760-1: 2006

Profile Features		Value ▲ Sn-Pb Assembly	Value ▲ Pb-free Assembly
Preheat temperature min.	$T_{s\ min}$	100 °C	100 °C
Preheat temperature typical	$T_{s\ typ}$	120 °C	120 °C
Preheat temperature max.	$T_{s\ max}$	130 °C	130 °C
Preheat time t_s from $T_{s\ min}$ to $T_{s\ max}$	t_s	70 seconds	70 seconds
Peak temperature	T_p	235 °C to 260 °C	245 °C to 260 °C
Time of actual peak temperature	t_p	Max. 10 seconds Max. 5 second each wave	Max. 10 seconds Max. 5 second each wave
Ramp-down rate min.		~ 2 °C/second	~ 2 °C/second
Ramp-down rate typical		~ 3.5 °C/second	~ 3.5 °C/second
Ramp-down rate max.		~ 5 °C/second	~ 5 °C/second
Time 25°C to 25°C		4 minutes	4 minutes

REVISION TABLE

Revision	Date	Status	Notes
001	30/09/2022	Initial release	Initial publication

DISCLAIMER

Except for the written expressed warranties, MGT does not implicitly, by assumption or whatever else, warrant, under-take, promise any other warranty or guaranty for any MGT product.

All information and technical specifications made available by MGT are for guidance only and we reserve the right to change or modify them without prior notice. Unless expressly stated in writing by MGT, we reject any guarantees, obligations, or warranties.

All MGT products with the technical specifications described are suitable for use in certain applications. Operating, production, storage and environmental conditions can have a massive influence on the parameters mentioned in the data sheets, which cause the performance to vary over time.

It is subject to the user's duty of care to design and validate his products in such a way that appropriate measures are taken, such as protective circuits or redundant systems to ensure the safety standards required in the application.

MGT components are not designed or rated for use in life support, rescue, safety critical, military, or aerospace applications where failure or malfunction could result in property or environmental damage, serious injury or death. In the aforementioned cases, please contact us before using MGT products.

In principle, we reserve all rights and MGT's general terms and conditions apply. You can find them on our website www.mgt.co.com.